

# Unitized Frame

## Tables & Desks

You can depend on this rugged yet refined table to stand up to the most demanding classroom challenges, including science spaces. Height adjustability, mobility and technology options accommodate different users and purposes while enabling easy reconfiguration within or between rooms. Dent-resistant, welded steel frames impart exceptional strength and stability.



### FIXED HEIGHT

- 29" high

### WORKSURFACE

- 1" thick worksurfaces except for Maple Block
- HPL (standard)
- TFL
- HPL Specialty
- Phenolic Resin
- Solid Maple Block (1-3/4" thick)
- Rectangle shape with square corners
- Plane shape with rounded corners

### FRAME AND LEGS

- Fully welded
- Perimeter rectangle tubular frame under perimeter of worksurface.
- Perimeter frame is 3-sided on tops 30" wide or less
- Perimeter frame is 4-sided on tops 36"-72" wide
- Square tube legs for rectangle tops
- Rounded tube legs for other tops
- See ADJUSTABLE HEIGHT for other features

### MOBILITY

- 1.5" diameter levelers - all legs
- 2" diameter levelers - all legs (square legs with phenolic or maple block worksurface material)
- Wheelbarrow - 75mm casters and 1.5" diameter levelers
- 75mm casters - all locking
- 5" casters - All locking (square leg only)

### SHIPPING

- Worksurfaces ship stacked, separate from frame/leg assembly, unless table is specified assembled
- Frame/leg assemblies ship stacked, unless tables is specified assembled
- Levelers or caster stems installed on legs
- Casters field installed



#### **ADJUSTABLE HEIGHT**

- 20"-28" high
- 24"-32" high

#### **KEY FEATURES**

##### **No side or foot rail bar standard on:**

- 20"-28" high - no visible adjustment holes between 20"-23" heights
- 24"-32" high - no visible adjustment holes
- 1" height adjustment increments
- Tamper resistant, dual height adjustment system



#### **ADJUSTABLE HEIGHT WITH SIDE RAILS**

- 29"-42" high

#### **KEY FEATURES**

##### **Side rail bar standard on:**

- Adjustment holes may be visible below 34" height
- 29"-42" - Potential visible adjustment holes between
- 1" height adjustment increments
- Tamper resistant, dual height adjustment system



#### **ADJUSTABLE HEIGHT WITH SIDE AND FOOT RAILS**

- 29"-42" high (with 36", 42", or 48" deep worksurface. All worksurface depths)
- 34"-42" high

#### **KEY FEATURES**

- Side rail & foot rail are 8.5" above the floor
- Foot rail bar is centered between legs
- Foot rail diameter is 1.25"
- 1" height adjustment increments
- Tamper resistant, dual height adjustment system